

EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L5	19	(program\$ adj transceive\$3).clm.	US-PGPUB	OR	ON	2006/08/18 12:31
L6	15	(program\$ adj (switch\$4 with circuit\$4)).clm.	US-PGPUB	OR	ON	2006/08/18 12:32
L8	92	(program\$ adj (a?D)).clm.	US-PGPUB	OR	ON	2006/08/18 12:33
L9	0	(program\$ adj (a\$1D with convert\$4)).clm.	US-PGPUB	OR	ON	2006/08/18 12:33
L10	0	(program\$ adj (fpaa)).clm.	US-PGPUB	OR	ON	2006/08/18 12:42
L11	45	(block with diagram and ((configurabl\$4 program\$) and (hardware))).clm.	US-PGPUB	OR	ON	2006/08/18 12:40
L12	0	(program\$ adj ((field with program\$ with analog with array) fpaa)).clm.	US-PGPUB	OR	ON	2006/08/18 12:43


 - 1998

[Advanced Scholar](#)
[Scholar Preference](#)
[Scholar Help](#)

Scholar Results 1 - 10 of about 90 for block diagram hardware architecture file programmable transceiver.

[All articles](#) [Recent articles](#)

A programmable CDMA IF transceiver ASIC for wireless

communications - group of 2 »

L Philips, I Bolsens, H De Man, L IMEC - Custom Integrated Circuits Conference, 1995., Proceedings of ..., 1995 - [ieeexplore.ieee.org](#)

... **Transceiver** functionality The PMCM functional **block diagram** is shown ... IF is done in the upcon- verter **block**. ... optimiza- tions such as **hardware** sharing, retiming ...

[Cited by 4](#) - [Web Search](#)

Integrated circuit technologies for wireless communications - group of 2 »

B Daneshrad - Personal, Indoor and Mobile Radio Communications, 1998. The ..., 1998 - [ieeexplore.ieee.org](#)

... rake receivers has dictated a different **hardware architecture**. ... mag- Page 4 / Register

File \ Data Arithmetic Unit Figure 5. **Block Diagram** of dual ...

[Cited by 3](#) - [Web Search](#) - [BL Direct](#)

A function specific EPLD for the PS/2 Micro Channel Bus adapter

YF Chan, CY Hung, C Hsiao, P Wong, N Lee, C ... - Custom Integrated Circuits Conference, 1989., Proceedings of ..., 1989 - [ieeexplore.ieee.org](#)

... The EPB200I **architecture** is designed to provide all ... 3 EPB2001 **BLOCK DIAGRAM USER CONFIGURATION** EPRA technology ... ports to control specific **hardware** functions on ...

[Web Search](#)

Cheops: a reconfigurable data-flow system for video processing - group of 12 »

VM Bove Jr, JA Watlington - Circuits and Systems for Video Technology, IEEE Transactions ..., 1995 - [ieeexplore.ieee.org](#)

... are then embodied in specialized **hardware** provided with ... convolution, correlation, matrix algebra, **block** transforms, spatial ... 2. Highly simplified **diagram** of the ...

[Cited by 52](#) - [Web Search](#) - [BL Direct](#)

VLSI implementation of digital receivers for paging and PCS - group of 2 »

R Subramanian, M Barberis, H Dawid, KJ Koch - Personal, Indoor and Mobile Radio Communications, 1997.' ..., 1997 - [ieeexplore.ieee.org](#)

... 2: The VLSI **Architecture** Exploration Space ... the design across a particular **hardware** software boundary. ... approach is to convert the **block diagram** description of ...

[Web Search](#)

Real-time OS based radar controller for multi-mode phased array radar system - group of 4 »

YC Hwang, DH Hong, YK Kwag - Radar 97 (Conf. Publ. No. 449), 1997 - [ieeexplore.ieee.org](#)

... **Hardware architecture** of the radar controller is shown in f ... Figure 5 shows a **block diagram** of main task ... composed of tracking filter, file management, interrupt ...

[Web Search](#) - [BL Direct](#)

Implementation of a wideband CDMA mobile communication testbed - group of 2 »

LC de Silva, Z Liu, WC Wong - Military Communications Conference, 1998. MILCOM 98. ..., 1998 - [ieeexplore.ieee.org](#)

... 3 Tx—our 591 Figure 2. **Block Diagram** of the ... Figure 3. **Architecture** of the ASTRA Development Board [2 ... filter, gain control and upconversion **hardware**, if an ...

[Web Search](#) - [BL Direct](#)

A low-power 128-tap digital adaptive equalizer for broadband modems - group of 2 »

CJ Nicol, P Larsson, K Azadet, JH O'Neill - Solid-State Circuits, IEEE Journal of, 1997 - ieeexplore.ieee.org

... The slicer **block diagram** is shown in Fig ... are mapped onto the positive to halve the comparison **hardware**. ... The log base-2 **block** is implemented by first extracting ...

[Cited by 60](#) - [Web Search](#) - [BL Direct](#)

[A real-time MPEG encoder using a **programmable processor** - group of 2 »](#)

D Kim, J Young, S Milton, HJ Kim, Y Kim - Consumer Electronics, IEEE Transactions on, 1994 - ieeexplore.ieee.org

... UWGSP5 **Architecture** Figure 2 is a **block diagram** of the ... simulations of the UWGSP5 **architecture** through a combination of Verilog **hardware** description language ...

[Cited by 8](#) - [Web Search](#) - [BL Direct](#)

[AlphaServer 4100 cached processor module **architecture** and design - group of 8 »](#)

MB Steinman, GJ Harris, A Kocev, VC Lamere, RD ... - Digital Technical Journal, 1996 - research.compaq.com

... In the **block diagram** shown in Figure 1, the microprocessor ... To speed up this process, a **hardware** data buffer ... registers can hold the entire cache **block** (512 bits ...

[Cited by 7](#) - [View as HTML](#) - [Web Search](#) - [BL Direct](#)

Google

Result Page: [1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [Next](#)

[Google Home](#) - [About Google](#) - [About Google Scholar](#)

©2006 Google